## **AMENDMENT AND PRESENTATION OF CLAIMS**

Please replace all prior claims in the present application with the following claims, in which claims 1, 6, 8, 15, and 17 are currently amended, claims 7 and 16 are canceled without prejudice or disclaimer, and no claims are withdrawn or newly presented.

1. (Currently Amended) A <u>computer implemented</u> method for accessing an instance of a recreatable object in a shorter-duration memory based on a reference located in a longer-duration memory, wherein the shorter-duration memory is associated with a call, the method comprising the steps of:

locating, within the shorter-duration memory, a context structure associated with the call;

locating an XREF pointers array based on data cached within the context structure;

- determining whether the XREF pointers array includes a pointer associated with said reference located in the longer-duration memory; and
- if the XREF pointers array includes a pointer associated with said reference located in the longer-duration memory, then following said pointer to locate said instance within said shorter-duration memory.
- 2. (Previously Presented) The method of Claim 1 wherein the step of locating an XREF pointers array based on data cached within the context structure comprises the steps of:
  - determining a hash code associated with a memory page in which the reference located in the longer-duration memory is located;
  - using at least a portion of the hash code as an index to locate an array entry within an array stored within the context structure; and

if said array entry contains a pointer, then following said pointer stored in said array entry to locate said XREF pointers array.

3. (Original) The method of Claim 2 wherein:

the array is a power-of-two array; and

the portion of said hash code that is used as said index includes a particular number of bits of said hash code.

4. (Original) The method of Claim 1 wherein:

the XREF pointers array does not include a pointer associated with said reference; and the method further comprises the steps of creating said instance by activating said recreatable object; and

storing a pointer to said instance in said XREF pointers array.

5. (Original) The method of Claim 2 wherein:

if said array entry does not contain a pointer, then creating said instance by activating said recreatable object; and

storing a pointer to said instance in said array entry.

6. (Currently Amended) A <u>computer implemented</u> method for accessing an instance of a recreatable object in shorter-duration memory based on a reference located in a longer-duration memory, wherein the shorter-duration memory is associated with a call, the method comprising the steps of:

when a class is activated, generating, within said shorter-duration memory, a class object associated with the class;

- storing, within said class object, data for locating instances of recreatable objects associated with said class, wherein said data includes a pointer to an XREF pointers array;
- to dereference said reference located in the longer-duration memory, performing the steps of determining that said reference located in a longer-duration memory is associated with said class; and

using said data within said class object to locate said instance of said recreatable object.

## 7. (Canceled)

- 8. (Currently Amended) The method of Claim 7 6 wherein the step of using said data within object to locate said instance includes the steps of:
  - determining whether the XREF pointers array includes a pointer associated with said reference;
  - if the XREF pointers array includes a pointer associated with said reference, then following said pointer to locate said instance within said shorter-duration memory.
  - 9. (Original) The method of Claim 8 wherein:
  - the XREF pointers array does not include a pointer associated with said reference; and the method further comprises the steps of
    - creating said instance by activating said recreatable object; and storing a pointer to said instance in said XREF pointers array.

10. (Previously Presented) A computer-readable medium carrying instructions for accessing an instance of a recreatable object in a shorter-duration memory based on a reference located in a longer-duration memory, wherein the shorter-duration memory is associated with a call, the computer-readable medium comprising instructions for performing the steps of:

locating, within the shorter-duration memory, a context structure associated with the call; locating an XREF pointers array based on data cached within the context structure;

- determining whether the XREF pointers array includes a pointer associated with said reference located in the longer-duration memory; and
- if the XREF pointers array includes a pointer associated with said reference located in the longer-duration memory, then following said pointer to locate said instance within said shorter-duration memory.
- 11. (Previously Presented) The computer-readable medium of Claim 10 wherein the step of locating an XREF pointers array based on data cached within the context structure comprises the steps of:
  - determining a hash code associated with a memory page in which the reference located in the longer-duration memory is located;
  - using at least a portion of the hash code as an index to locate an array entry within an array stored within the context structure; and
  - if said array entry contains a pointer, then following said pointer stored in said array entry to locate said XREF pointers array.

12. (Original) The computer-readable medium of Claim 11 wherein:

the array is a power-of-two array; and

the portion of said hash code that is used as said index includes a particular number of bits of said hash code.

13. (Original) The computer-readable medium of Claim 10 wherein:

the XREF pointers array does not include a pointer associated with said reference; and the computer-readable medium further comprises instructions for performing the steps of creating said instance by activating said recreatable object; and storing a pointer to said instance in said XREF pointers array.

14. (Original) The computer-readable medium of Claim 11 further comprising instructions for performing the steps of:

if said array entry does not contain a pointer, then creating said instance by activating said recreatable object; and

storing a pointer to said instance in said array entry.

15. (Currently Amended) A computer-readable medium carrying instructions for accessing an instance of a recreatable object in shorter-duration memory based on a reference located in a longer-duration memory, wherein the shorter-duration memory is associated with a call, the computer-readable medium comprising instructions for performing the steps of:

when a class is activated, generating, within said shorter-duration memory, a class object associated with the class;

storing, within said class object, data for locating instances of recreatable objects associated with said class, wherein said data includes a pointer to an XREF pointers array;

to dereference said reference located in the longer-duration memory, performing the steps of determining that said reference located in the longer-duration memory is associated with said class; and

using said data within said class object to locate said instance of said recreatable object.

## 16. (Canceled)

- 17. (Currently Amended) The computer-readable medium of Claim 16 15 wherein the step of using said data within object to locate said instance includes the steps of:
  - determining whether the XREF pointers array includes a pointer associated with said reference;
  - if the XREF pointers array includes a pointer associated with said reference, then following said pointer to locate said instance within said shorter-duration memory.
  - 18. (Original) The computer-readable medium of Claim 17 wherein: the XREF pointers array does not include a pointer associated with said reference; and

the computer-readable medium further comprises instructions for performing the steps of creating said instance by activating said recreatable object; and storing a pointer to said instance in said XREF pointers array.

- 19. (Previously Presented) The method of Claim 1 wherein the duration of the shorter-duration memory is shorter than the duration of the longer-duration memory.
  - 20. (Previously Presented) The computer-readable medium of claim 10 wherein the duration of the shorter-duration memory is shorter than the duration of the longer-duration memory.